



Integral Waterpruf

AMTECO INTEGRAL WATERPRUF is a heavy duty liquid admixture produced especially for complete waterproofing of mass and reinforced concrete structures, ready-mixed and precast concrete. Does not contain calcium chloride to speed up setting time of cement or cause corrosion to stressing wire in prestressed concrete.

AMTECO INTEGRAL WATERPRUF 是一种有效的双料水性混合料，专制为洋灰水泥整体防水并增加坚强紧密，使混凝土能充分永久防水。适用于各种洋灰制“造业。预应力混凝土中的钢丝。氯化物可以加快水泥凝结时间或导致腐蚀预应力混凝土中的钢丝。”

AMTECO INTEGRAL WATERPRUF adalah campuran cecair tugas berat yang dihasilkan terutamanya untuk kalis air yang lengkap dan konkrit bertetulang struktur, konkrit siap bina. Tidak mengandungi kalsium klorida untuk mempercepatkan penetapan masa simen atau menyebabkan kakisan menegaskan dawai dalam konkrit prategasan.

Advantage

- Improve workability and plasticity of the mix.
- Reduces water absorption and penetration.
- Reduces possibility of shrinkage and consequential cracking.
- Facilitates compaction and increases compression and tensile strength.

Mixing

AMTECO INTEGRAL WATERPRUF mix cement with necessary aggregates in the usual way. Put straight into the mixer or to the gauging water at the rate of 500ml per 50kg cement. The water / cement ratio should be kept as low as possible. For consistent workability, we recommend about 10% of gauging water used. Suggested to stir well before application.

Instruction For Use

Safety

Impervious gloves and barrier cream should be used when handling these products. Eye protection should be worn. In case of contact with eye, wash thoroughly with plenty of water and seek medical advice if symptoms persist. If contact with skin occurs. It must be removed before curing takes place. Wash off with an industrial skin clearer followed by plenty of soap and water. Do not use solvent. Ensure adequate ventilation when using those products.

Fire

AMTECO INTEGRAL WATERPRUF is water based and non-flammable.

Packing

4 litre/jar
20 litre/pail

TECHNICAL DATA	
Foam	Liquid
Appearance	Dark Brown
Specific Gravity	Typical 1.03
Shelf life	12 months when unopened in original packing and stored in a dry cool place.
Note : Consumption may vary depending on surface conditions and application technique.	

