



Quikcure Accelerator

AMTECO QUIKCURE ACCELERATOR is a liquid setting accelerator which will speed up setting time and increases early strength when incorporated in cement / concrete mix. The workability of the mix is further improved / enhanced by allowing water cement ratio to be reduced if required.

AMTECO QUIKCURE ACCELERATOR 是水性液体混合料，参与洋灰/混凝土混合时发挥极佳效能，快速硬化，并提早加强粘合力 and 刚性，能降低水与洋灰混合比，使工作顺畅。

AMTECO QUIKCURE ACCELERATOR adalah sejenis cecair pengadun simen yang sangat mantap apabila dicampur dengan simen/konkrit. Ia berupaya mempercepatkan masa pengerasan simen dan meningkatkan kekuatan awal. Kesesuaian bahan campuran ini dapat membantu memperbaiki lagi daya kerja serta mengurangkan air/simen jika diperlukan.

Advantage

- Allows faster demoulding of precast work.
- Increases compression and tensile strength.
- Improves workability and plasticity or water / cement mix.
- Allows plasticising and rapid hardening process.

Mixing

AMTECO QUIKCURE ACCELERATOR dosage is 500ml per 50kg of cement according to the setting time required. The quantity should be mixed with 10 litres of water where cement is then added. Add more water if required.

Instruction For Use

Safety

Impervious gloves and barrier cream should be used when handling these products. Eye protection should be worn. In case of contact with eye, wash thoroughly with plenty of water and seek medical advice if symptoms persist. If contact with skin occurs. It must be removed before curing takes place. Wash off with an industrial skin clearer followed by plenty of soap and water. Do not use solvent. Ensure adequate ventilation when using those products.

Fire

AMTECO QUIKCURE ACCELERATOR is water based and non-flammable.

Packing

4 litre/jar
20 litre/pail

TECHNICAL DATA	
Foam	Liquid
Appearance	Light Brown
Specific Gravity	Typical 1.30 ± 0.02
Shelf life	12 months when unopened in original packing and stored in a dry cool place.
Note : Consumption may vary depending on surface conditions and application technique.	

